



i20-T Door Phone



Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司

HQ Add: Level 3, Block A, Gaoxinqi Building, Anhua Industrial Park, Qianjin 1 Road, 35th District, Bao'An, Shenzhen, 518101 P.R. China 地址:深圳市宝安35区前进一路安华工业区高新奇大厦A座三楼,518101

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: fanvil@fanvil.com www.fanvil.com Beijing Tel:+86-10-5753-6809 Suzhou Tel: +86-512-6592-0605 SEA Tel: +60-3-203-50737



1、Description

i20-T Voice Access control is a digital IP door phone with Fanvil Voip Solutions (Broadcom chip 1190), stable and reliable. FDSP ensure voice loud and clear. Good looking , durable, easy to install, comfortable buttons, and low power consumption.

2. Basic Function

- Support G.711,G.729, etc. Codec voice intercom;
- Support SIP 2.0(RFC3261) and related RFC protocol
- Unlock function (swipe or communication)
- Visitor leave message;
- Calling indoor extension for two-way conversation;
- Software upgrading on line;
- WEB remote management of Terminal malfunction or status;

3, Specification

Communication protocol		SIP 2.0(RFC-3261)	
	Master Chip	Broadcom 1190	
Keys	Design	Stainless steel	
	Direct-button	1	
	Numeric Keypad	Optional	
	Microphone	1	
	Amplifier	1.5W	
Voice	Speaker	1.5W	
	Volume Control	Adjustable	
	FDSP	Support(AEC)	
Voice streem	Supportable Protocol	RTP	
voice stream	Voice stream CODEC	G.711, G.729	
	Power Supply	12V+-15%/1A DC or PoE	
	РоЕ	PoE 802.3af (Class 0 - 12.95W) 48V/380mA	
	LAN	10/100BASE-TX s Auto-MDIX, RJ-45)	
	Cables	HSYV or better	
Port	Passive Switch	Normally Open and Normally Closed highest at 30V/1A AC/DC	
	Active Switched Output	12V/500mA DC	
	RS232	Supported	
RFID/IC Card	EM-40XX (125Khz)	Supported	

Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司



Reader			
	Shell Material	Aluminum Cover、 Plastic back case	
	Operating Temperature	0°C to 55°C	
	International Protection	IP53	
	Working Condition	10% - 95%	
Structure	Relative Humidity	10% - 93%	
	Storage Temperature	-40°C to 70°C	
	Installation	Embedded installation (pre-burying)	
	Size	Overall Dimension: $174.5 \times 96 \times 44$ mm pre-burying	
		Mounting Dimension: $148 \times 80 \times 36$ mm	


4. Schematic Diagram



Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司



5.System CompositionDiagram



System Composition Diagram

• Web Business Management

It is mainly used for remote management i20-T voice access device, which includes such features as the device parameter management, access control parameter settings, card, log management.

Access Control

Access control is consist of i20 voice access control, exclusive DC power supply and electric lock . Inside of i20-T, self-powered electric lock can directly drive the starting current of 500mA power locks; additionally you can also access exclusive external DC power supply and the voice access output control signals, to drive electric lock on and off by access exclusive DC power.

• Intercom function

i20-T voice intercom system consists of i20- access control, SIP phones, phones installed SIP soft-terminal, IPPBX . i20-T Voice Access supports standard SIP protocol, and has good system compatibility with main IPPBX in the market.

Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司





6 、 Functions

Functions			Application
	Intercom	Resident voice intercom	Intercom between residents and visitors
	Open the door	Remote Door	Both Sip terminals and phones can open the door when ring or speak
	open the door	Swipe	Swipe at RF ID area, the door will be open after valid confirmation
	Timeout Handling	Calling Timeout	When calling timeout, the terminal does not answer, the I20-T Voice Access automatically hang up
Software Functions		Conversation timeout	When conversation between i20 voice access and terminal is timeout, I20 automatically hang up
	Incorrect handling	Fault Tips	Equipment failure, the speaker needs to have tips
	Property management	Front Monitoring	If monitoring function activate, the user terminal can hear the voice situation of door
	Terminal	Query and device settings	Remote checking and setting device parameters and status via internet
	Management	Running Log	I20-T Record device running logs
	Project maintenance	I20-T Setting function	During installation and commissioning, you can set up the device through the key parameter
	Network Access	Access to Internet	When equipment power on, select 2 ways to access to internet(dynamic or static IP)
	Request	Access to IPPBX	According to user SIP account and password, Device registered on the specified IPPBX
		Keys	Support Talkback (1 or 2 buttons)
		Numeric keypad	For the numeric keypad dialing or opening the door via password
		RFID Card reader	For swiping to open the door
		Speaker	For intercom audio, voice prompts, the alarm tone or an error, success prompt
		Microphone	Visitor's voice input
Hardware function		Door lock Controller	Control on/off of lock(Initially output switch control signal only

Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司



	Ethernet Port	Debug connection to internet and lan, support POE
		power-up
	Power Port	Input 12V, power supply for I20-T
	Indicator	Indicate status of I20-T Access Control
	Function Jumper	Setting output mode of door lock
	Reset	Press * (on the motherboard) button for 5 seconds to
		restore factory settings
	Voice Reporting No.	Press # (on the motherboard) button for 5 seconds, to
		start voice reporting IP function
Physical Function	Waterproof	Splashing to panel does not affect the normal
		operation of the system
	Operating	$0\sim$ 55 Degree
	Temperature	

Fanvil Technology Co., Ltd 深圳方位通讯科技有限公司